



ADDITIONAL RUNWAY INFORMATION						
RWY		RVR	USABLE LENGTHS		TAKE-OFF	WIDTH
			Threshold	LANDING BEYOND Glide Slope		
14L	HIRL (60m) CL (15m)	RVR	NA		②	197'
32R	HIRL (60m) CL (15m) HIALS-II TDZ PAPI(3.0°) ①	RVR	9843' 3000m	8932' 2722m	NA	60m
① HSTIL-K5 & K4 ② <u>TORA RWY 14L:</u> From rwy head 11,483'(3500m) twy K3 int 10,761'(3280m)						
14R	HIRL (60m) CL (15m)	RVR	NA		④	197'
32L	HIRL (60m) CL (15m) HIALS-II TDZ PAPI(3.0°) ③	RVR	10,039' 3060m	9067' 2764m	NA	60m
③ HSTIL-L7, L5, L4, L3 & L2 ④ <u>TORA RWY 14R:</u> From rwy head 13,084'(3988m) twy L1 int 11,995'(3656m) twy LF int 10,860'(3310m)						
18L	HIRL (60m) CL (15m) HIALS-II TDZ PAPI(3.0°) ⑥	RVR	9843' 3000m	8871' 2704m	NA	197'
⑤ 36R	HIRL (60m) CL (15m)	RVR	NA		⑦	60m
⑤ RWY with antiskid layer. ⑥ HSTIL-Y5 & Y4 ⑦ <u>TORA RWY 36R:</u> From rwy head 11,483'(3500m) twy Y2 int 11,302'(3445m) twy Y3 int 10,974'(3345m)						
18R	HIRL (60m) CL (15m) HIALS-II TDZ PAPI(3.0°) ⑨	RVR	11,040' 3365m	9962' 3036m	NA	197'
⑧ 36L	HIRL (60m) CL (15m)	RVR	NA		⑩	60m
⑧ RWY with antiskid layer. ⑨ HSTIL-Z10, Z8 & Z7 ⑩ <u>TORA RWY 36L:</u> From rwy head 13,711'(4179m) twy Z6 int 12,205'(3720m)						
<b>Standard TAKE-OFF ①</b>						
<b>Rwys 14L/R, 36L/R</b>						
<b>LVP must be in Force</b>						
Approved Operators	HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
C	125m	150m	200m	250m	400m	500m
D	150m	200m	250m	300m		
① Operators applying U.S. Ops Specs: CL required below 300m; approved HUD required below 150m.						